SAFETY DATA SHEET

Canadian Krown Dealers Inc. 35 Magnum Dr. Schomberg, Ontario, L0G 1T0 Canada (905)939-8750 / 1(800)267-5744

PRODUCT: Krown T32 All Purpose Lubricant - 400 g

SECTION 01: IDENTIFICATION

Product Item Numbers Product Identity Manufacturer	Krown T32 All Purpose Lubricant - 400 g
24 hour emergency telephone number	In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800) 424-9300.
Recommended Use Chemical Family	Lubricant, Penetrant, Rust Inhibitor.

SECTION 02: HAZARD IDENTIFICATION



_abel Elements: Signal Word Hazard Classification:	DANGER.
Physical Hazards Health Hazards	Flammable Aerosols - Category 1. Gases Under Pressure - Liquefied Gas .
Health Hazards	Not Classified.
Hazard Statement	H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated (1). H280:Contains gas under pressure; may explode if heated (L).
Precautionary Statements:	
Prevention	P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not pierce or burn, even after use.
Response	None .
Storage	P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. P403:Store in a well ventilated place.
Disposal	P501:Dispose of contents/container in accordance with local, regional, national, and/or international regulations.
Hazard(s) not otherwise classified (HNOC)	
Classifièd according to:	Canada's Hazardous Products Act/Hazardous Products Regulations (WHMIS 2015) and Occupational Safety and Health Administration (OSHA).

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS		
HAZARDOUS INGREDIENTS	CAS #	WT. %
Isobutane	75-28-5	10-30
Propane	74-98-6	7-13

SECTION 04: FIRST-AID MEASURES

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.
Skin Contact	Immediately flush the contaminated skin with soap and water. If this chemical penetrates clothing, immediately remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention.
Eye Contact	Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.
Ingestion Most important symptoms/effects, acute and delayed	If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting.

τεςις

CODE: KR-002009

SAFETY DATA SHEET

PRODUCT: Krown T32 All Purpose Lubricant - 400 g

SECTION 04: FIRST-AID MEASURES

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 05: FIRE-FIGHTING MEASURES

	General Fire Hazards	separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do. Flammable.
	Special Protective Equipment and Precautions for Firefighters	Organic Compounds. Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water
ι	Suitable Extinguishing Media Unsuitable Extinguishing Media Specific Hazards Arising from the Chemical	In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified

SECTION 06: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).
Methods and Materials for Containment and Cleaning Up	
Environmental Precautions	Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

SECTION 07: HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing vapours or mists. Never pierce, drill, grind, cut, saw or weld any empty container. Do not eat or drink while working. See Section 08 for Protective Personal Equipments.

Conditions for Safe Storage including any Incompatibilities

Equipments. Keep container tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, and flame. Do not store in direct sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	OSH/ PEL	A PEL STEL	NIOSH REL
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Appropriate Engineering Individual Protection Mea Eye/Face Protection Skin Protection Respiratory Protection	asures:	Local exhaust ventilation of Value if unprotected perso showers are available. Chemical splash goggles Use appropriate protective	onnel are involved. En are recommended.	sure that eyewash station	
Thermal Hazards General Hygiene Considerations		None Known. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment prior to use.			

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Form	Aerosol.
Physical Appearance	Red.
Odor	N/A.
Odor Threshold (ppm)	
Specific Gravity	0.880-0.920.
Vapour Density (Air=1)	Heavier than air.
Aerosol Vapour Pressure (psig, 21°C)	70-90 .
pH	N/A.
Boiling Point liquid (°C)	-11.72°C (10.9°F). (For propellant).
Melting/Freezing Point (°C)	
Flash Point (°C), Method	Closed cup: -83.15 °C (-117.7 °F). (For propellant).

Powered by

ECIS

CODE: KR-002009

Page 2

PRODUCT: Krown T32 All Purpose Lubricant - 400 g

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Flashback	
Evaporation Rate (n-Butyl Acetate = 1)	
VOC Content	N/A.
Solubility in water	N/A.
Auto Ignition Temperature (°C)	460°C (860°F). (Propellant).
Lower Flammable Limit (% Vol)	1.8. (Propellant).
Upper Flammable Limit (% Vol) Coefficient of Water/Oil Distribution	
Coefficient of Water/Oil Distribution	N/A.```´´
Viscosity	N/A.

SECTION 10: STABILITY AND REACTIVITY

Reactivity	
Chemical Stability	;
Possibility of Hazardous Reactions	ļ
Conditions to Avoid	ļ
Incompatible Materials	
Hazardous Decomposition Products	ļ
•	

No hazardous reactions. Stable under the recommended storage and handling conditions. It may catch fire on contact with oxidizing mineral acids. Heat, flames, sparks. None known. In combustion emits toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Isobutane	658 mg/L (Rat - 4hrs)	Not available
Propane	658 mg/L (Rat - 4hrs)	Not available
Information on Likely Routes of Exposure: Routes of entry - Inhalation Routes of entry - Skin & Eye Routes of entry - Ingestion Routes of entry - Skin Absorption Symptoms Related to the Physical, Chemical and Toxicological Characteristics Acute Toxicity Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Respiratory or Skin Sensitization Germ Cell Mutagenicity Carcinogenicity Reproductive Toxicity STOT - Single Exposure STOT - Repeated Exposure Aspiration Hazard Chronic Effects		

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity	
not be released into the environment.	
Persistence and degradability The product itself has not been tested.	
Bioaccumulation Potential The product itself has not been tested.	
Mobility in Soil The product itself has not been tested.	
Other Adverse Effects None Known.	

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods.....

This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG (Canada- Road)
DOT (US-Road)
IMDG (International- Marine)
IATA (International- Air)

UN1950, AEROSOLS, Class 2.1. UN1950, AEROSOLS, Class 2.1, LTD QTY, Consumer Commodity ORM-D. UN1950, AEROSOLS, Class 2.1. UN1950, AEROSOLS, Class 2.1, LTD QTY.



CODE: KR-002009

SAFETY DATA SHEET

CODE: KR-002009

PRODUCT: Krown T32 All Purpose Lubricant - 400 g

SECTION 15: REGULATORY INFORMATION

Canada Regulations:	WHMIS Classification. A: Compressed gas. B5: Flammable aerosol.
Canadian Environmental Protection Act	All ingredients listed appear on the Domestic Substances List (DSL).
inv	Environmental Protection Act: Constituents of this product are included on the TSCA inventory. This product is considered hazardous under the OSHA Hazard Communication Standard.

SECTION 16: OTHER INFORMATION

Disclaimer	The information contained herein is based on data considered accurate. No guarantee or warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. The SDS provider assumes no responsibility for personal injury or property damage to vendors or users or third parties, caused by the material. Such vendors or users assume all risks with the use of the material. This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all the information required by the CPR.
Abbreviations	ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.
Prepared by Latest Revision	Regulatory Affairs OCT 04/2018

