Canadian Krown Dealers Inc. 35 Magnum Dr. Schomberg, Ontario, LOG 1T0 Canada (905)939-8750 / 1(800)267-5744

Krown The Solution - 400 g PRODUCT:

**SECTION 01: IDENTIFICATION** 

Empack Spraytech Inc. Manufacturer.....

Product Item Numbers..... KR-002010

Product Identity......24 hour emergency telephone number..... Krown The Solution - 400 g CANUTEC: 1-613-996-6666.

Recommended Use..... Penetrating oil. Chemical Family..... Mixture.

## **SECTION 02: HAZARD IDENTIFICATION**



Label Elements:

Signal Word..... WARNING.

Hazard Classification:

Physical Hazards..... Flammable Aerosols - Category 2. Gases Under Pressure - Liquefied Gas.

Health Hazards..... Not Classified. Environmental Hazards..... Not Classified.

Hazard Statement..... H223:Flammable aerosol. H229:Pressurised container: may burst if heated (2).

H280:Contains gas under pressure; may explode if heated (L).

Precautionary Statements:

Prevention..... P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not

CODE: KR-002010

pierce or burn, even after use.

Response..... None

P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. Storage.....

P403:Store in a well ventilated place.

None.

Hazard(s) not otherwise classified (HNOC) None Known.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS					
CHEMICAL NAME AND SYNONYMS	CAS#	WT. %			
Isobutane	75-28-5	10-30			
Propane	74-98-6	7-13			
Barium Sulfonate	61790-48-5	1-5			

### **SECTION 04: FIRST-AID MEASURES**

Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain
Skin Contact	immediate medical assistance. Immediately flush the contaminated skin with soap and water. If this chemical penetrates
	clothing, immediately remove the clothing and flush the skin with water. If irritation persists after washing, get medical attention.
Fire Orintant	3, g
Eye Contact	Check for and remove contact lenses. Immediately flush eyes with water for a minimum of

15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. Do not induce vomiting, get medical attention. Rinse mouth. Obtain medical advice.

N/A.

Most important symptoms/effects, acute ... and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

## PRODUCT: Krown The Solution - 400 g

## **SECTION 05: FIRE-FIGHTING MEASURES**

Suitable Extinguishing Media..... Dry chemical powder. Carbon dioxide. Foam, water spray or fog. Unsuitable Extinguishing Media..... Do not use water jet as an extinguisher, as this will spread the fire. Specific Hazards Arising from the Chemical In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified

Organic Compounds.

Special Protective Equipment and ..........

Firefighters must use standard protective equipment including flame retardant coat, helmet Precautions for Firefighters with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water

separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do.

**CODE: KR-002010** 

General Fire Hazards..... Flammable Aerosol.

### **SECTION 06: ACCIDENTAL RELEASE MEASURES**

Personal Precautions, Protective ..... No action shall be taken involving any personal risk or without suitable training. Evacuate Equipment and Emergency Procedures surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid

walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate

personal protective equipment (see Section 08).

Methods and Materials for Containment .. Wash with plenty of water.

and Cleaning Up

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent Environmental Precautions.....

environmental contamination.

## **SECTION 07: HANDLING AND STORAGE**

Avoid breathing vapours or mists. Never pierce, drill, grind, cut, saw or weld any empty Precautions for Safe Handling.....

container. Do not eat or drink while working. See Section 08 for Protective Personal

Conditions for Safe Storage including any Incompatibilities

Keep container tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, and flame. Do not store in direct sunlight.

# **SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	CGIH TLV STEL	OSH. PEL	A PEL STEL	NIOSH REL
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Barium Sulfonate	Not available	Not available	Not available	Not available	Not available
Appropriate Engineering Controls Local exhaust ventilation required to maintain the point of use below the Threshold Limit Value if unprotected personnel are involved. Ensure that eyewash stations and safety showers are available.					e Threshold Limit ons and safety
Individual Protection Measures: Eye/Face Protection		e clothing to avoid ski ood ventilation is mair or mists are generate Irink or smoke. Always ndling the material and	ntained. NIOSH approved d . s observe good persona d before eating, drinking	I hygiene measures,	

#### **SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Form	Aerosol.
Physical Appearance	Thin Blue Liquid.
Odor	Odorless.
Odor Threshold (ppm)	Not available.
Specific Gravity	0.510-0.800.
Vapour Pressure (psig)	>30.
pH	Not available.
Boiling Point (Propellant), ° C	-11.72°C (10.9°F). (Isobutane).
Melting/Freezing Point (°C)	Not available.
Flash Point (°C), Method	-82.78. Closed cup. (Propellant).
Flashback	Not available.
Evaporation Rate (n-Butyl Acetate = 1)	Not available.
VOC Content	NMT 25.
Solubility in water	Insoluble.
Auto Ignition Temperature (°C)	460°C (860°F). (Propellant).
,	, , , , , ,



LC50

**CODE: KR-002010** 

LD50

PRODUCT: Krown The Solution - 400 g

### **SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

Lower Flammable Limit (% Vol)..... 1.8. (Propellant). Upper Flammable Limit (% Vol)..... 8.8. (Propellant). Note..... NMT = Not More Than.

#### **SECTION 10: STABILITY AND REACTIVITY**

Reactivity ..... No hazardous reactions.

Chemical Stability..... Stable under the recommended storage and handling conditions.

Possibility of Hazardous Reactions..... It may catch fire on contact with oxidizing mineral acids.

Conditions to Avoid..... Heat, flames, sparks.

Incompatible Materials..... None known.

Hazardous Decomposition Products..... In combustion emits toxic fumes.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

658 mg/L (Rat - 4 hrs) Isobutane Not available Propane 658 mg/L (Rat - 4 hrs) Not available Not available **Barium Sulfonate** Not available

Information on Likely Routes of Exposure: Routes of entry - Inhalation..... Yes. Routes of entry - Skin & Eye..... Yes. Routes of entry - Ingestion..... Yes. Routes of entry - Skin Absorption..... Irritant effects.

Symptoms Related to the Physical, ........

**INGREDIENTS** 

Chemical and Toxicological Characteristics

Acute Toxicity..... No known significant effects. Skin Corrosion/Irritation..... Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation..... Not classified.

Respiratory or Skin Sensitization..... Not expected to be a skin or respiratory sensitizers.

No information is available, and no adverse effects are expected. Germ Cell Mutagenicity..... Carcinogenicity......Reproductive Toxicity..... Not classified as carcinogenic by ACGIH, IARC, OSHA or NTP. Based on available data, the classification criteria are not met.

STOT - Single Exposure..... Not classified. STOT - Repeated Exposure..... Not classified. Aspiration Hazard..... Not classified.

Chronic Effects..... No known adverse effects.

#### **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should not be released into the environment.

Persistence and degradability ..... The product itself has not been tested. Bioaccumulation Potential..... The product itself has not been tested. Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and

must be disposed of in accordance with current local, provincial and federal regulations.

#### **SECTION 14: TRANSPORT INFORMATION**

TDG (Canada- Road).....

UN1950, AEROSOLS, Class 2.1, Ltd. Qty. UN1950, AEROSOLS, Class 2.1, Ltd. Qty., Consumer Commodity ORM-D. DOT (US-Road).....

IMDG (International- Marine).....IATA (International- Air)..... UN1950, AEROSOLS, Class 2.1, Ltd. Qty. UN1950, AEROSOLS, Class 2.1, Ltd. Qty.

### **SECTION 15: REGULATORY INFORMATION**

Canada Regulations:.... Refer to Section 2 for a WHMIS 2015 Classification for this product. Canadian Environmental Protection Act ... All ingredients listed appear on the Domestic Substances List (DSL).

(CEPA)



## PRODUCT: Krown The Solution - 400 g

# **SECTION 15: REGULATORY INFORMATION**

US Regulations...... Environmental Protection Act: Constituents of this product are included on the TSCA inventory. This product is considered hazardous under the OSHA Hazard Communication Standard.

### **SECTION 16: OTHER INFORMATION**

ACGIH: American Conference of Governmental Industrial Hygienists; CAS: Chemical Abstract Service; NIOSH: National Institute for Occupational Safety and Health, OSHA: Occupational Safety and Health Administration- USA; TSCA: Toxic Substances Control Act 1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous Materials Information System STOT: Specific Target Organ Toxicity.

**CODE: KR-002010** 

Regulatory Affairs

